



### VANDAL PROOF OUTDOOR CAMERA



**SSR-B9D3/SSR-B9D6**

#### Basic Parameters

|                       |                 |
|-----------------------|-----------------|
| Image Sensor          | 1/3" Super DIS  |
| TV System             | PAL/NTSC        |
| Horizontal Resolution | 900TVL          |
| Lens                  | 3.6/6mm         |
| White Balance         | ATW/Manual/Auto |
| AGC                   | Auto/Manual/Off |
| Voltage               | DC12V(9V ~ 15V) |



**SSR-BV9D2112**

#### Basic Parameters

|                       |                 |
|-----------------------|-----------------|
| Image Sensor          | 1/3" Super DIS  |
| TV System             | PAL/NTSC        |
| Horizontal Resolution | 900 TVL         |
| Lens                  | 2.8-12mm        |
| White Balance         | ATW/Manual/Auto |
| AGC                   | Auto/Manual/Off |
| Voltage               | DC12V (9V~15V)  |
| Operating Temperature | -20°C~60° C     |

### IR DOME INDOOR CAMERA



**SSR-D6D3/SSR-D6D6**

#### Basic Parameters

|                       |                   |
|-----------------------|-------------------|
| Image Sensor          | 1/4" DIS          |
| TV System             | PAL/NTSC          |
| Horizontal Resolution | 600 TVL           |
| Lens                  | 3.6/6mm           |
| White Balance         | Auto              |
| Video Output          | 1Vp-p, 75ohm; BNC |
| Infrared distance     | 20-25 M           |
| Infrared leds         | 24 pcs IR leds    |
| Power                 | DC12V             |



**SSR-D9D3/SSR-D9D6**

#### Basic Parameters

|                       |                 |
|-----------------------|-----------------|
| Image Sensor          | 1/3" DIS        |
| TV System             | PAL/NTSC        |
| Horizontal Resolution | 900 TVL         |
| Lens                  | 3.6mm/6mm       |
| White Balance         | ATW/Manual/Auto |
| AGC                   | Auto/Manual/Off |
| Voltage               | DC12V (9V~15V)  |

### BULLET & DOME INDOOR CAMERA (SONY CCD & OSD)



**SSR-D7S3/SSR-D7S6**

#### Basic Parameters

|                       |                              |
|-----------------------|------------------------------|
| Image Sensor          | 1/3" SonySUPER<br>HAD CCD II |
| TV System             | PAL/NTSC                     |
| Horizontal Resolution | 700 TVL                      |
| Lens                  | 3.6/6mm                      |
| IR                    | 24pcs LED                    |
| IR Distance           | 20-25M                       |
| DNR                   | D-DNR                        |
| White Balance         | ATW/Manual/Auto              |
| Voltage               | DC12V (9V~15V)               |



**SSR-B7S3/SSR-B7S6**

#### Basic Parameters

|                       |                              |
|-----------------------|------------------------------|
| Image Sensor          | 1/3" SonySUPER<br>HAD CCD II |
| TV System             | PAL/NTSC                     |
| Horizontal Resolution | 700 TVL                      |
| Lens                  | 3.6/6mm                      |
| IR                    | 24pcs LED                    |
| IR Distance           | 30-35M                       |
| WDR                   | D-WDR                        |
| DNR                   | D-DNR                        |
| OSD                   | OSD                          |
| White Balance         | ATW/Manual/Auto              |
| AGC                   | Auto/Manual/Off              |
| Voltage               | DC12V (9V~15V)               |